

Stainless Steel MultiCartridge Filters

MICROMATCH 400

Series



FEATURES OF THE MICROMATCH 400


- + Commercial and Industrial Use
- + Drain and air vent NPT connections
- + 304 stainless steel housing, also available in 316 or 316L stainless steel
- + Accept complete range of filter media
- + Accept 9 3/4" cartridges
- + Use to filter: silt, taste, odor or sediment
- + Flanged inlet and outlet connections
- + Maximum operating pressure: 150 psi
- + Operating temperature: 40°-176°F (4°-80°C)

Model No.	Rated Capacity (GPM)	Dimensions (Inch)		Length of Cartridges (Inch)	No. of Cartridges PCS	Pipe Size (Inch)		
		Width	Height			Inlet/Outlet	Drain	Vent
MM4-5D1L	40	13-3/8	29-1/2	10	5	2	1/4" FNPT	1/4" FNPT
MM4-5D2L	80	13-3/8	39-1/3	20	5	2	1/4" FNPT	1/4" FNPT
MM4-5D3L	120	13-3/8	49-1/4	30	5	2	1/4" FNPT	1/4" FNPT
MM4-5D4L	160	13-3/8	59	40	5	2	1/2" FNPT	1/4" FNPT
MM4-7D1L	56	15-3/8	31-1/2	10	7	2	1/2" FNPT	1/4" FNPT
MM4-7D2L	112	15-3/8	41-1/3	20	7	2	1/2" FNPT	1/4" FNPT
MM4-7D3L	168	15-3/8	51-1/4	30	7	2	1/2" FNPT	1/4" FNPT
MM4-7D4L	224	15-3/8	61	40	7	2	1/2" FNPT	1/4" FNPT
MM4-12D3L	288	17-3/8	54-3/8	30	12	3	3/4" FNPT	1/4" FNPT
MM4-12D4L	384	17-3/8	63-3/4	40	12	3	3/4" FNPT	1/4" FNPT
MM4-15D3L	360	20-7/8	56	30	15	3	3/4" FNPT	1/4" FNPT
MM4-15D4L	480	20-7/8	65-3/8	40	15	3	3/4" FNPT	1/4" FNPT
MM4-19D3L	456	22	57-1/2	30	19	4	3/4" FNPT	1/4" FNPT
MM4-19D4L	608	22	67	40	19	4	3/4" FNPT	1/4" FNPT
MM4-27D3L	648	24-3/4	60-1/4	30	27	4	3/4" FNPT	1/4" FNPT
MM4-27D4L	864	24-3/4	69-3/4	40	27	4	3/4" FNPT	1/4" FNPT

* Specifications are subject to change without notice

Metric Units	Flowrate (m ³ /hr) = GPM / 4.4	Media (m ³) = ft ³ / 35.3	Weight (Kg) = lbs / 2.2	Dimensions (mm) = inch x 25.4
--------------	---	--	-------------------------	-------------------------------

* Flow shown are based on a maximum flow of 8GPM per sediment cartridge or are limited by the connection size.



EnviroMatch, Inc.
Water and Wastewater Treatment Systems

41601 Cherry Street #B
Murrieta, CA 92562, USA
www.enviromatch.com

Tel: +1-949-340-2715
Fax: +1-949-340-2060
sales@enviromatch.com

Exclusive Agent: